

6507/G2+ touch panel



Reference: 6507/G2+
Product code: 12226507A
EAN code: 8429898029740



Main characteristics

- Touch panel with G2+ technology of two non-polarised wires.
- Vandal resistant (IK-10) and weatherproof (IP-65) panel made of 6mm thickness aluminium.
- 2MPx HD 130° wide angle camera with white self-starting LEDs for night vision.
- 7" TFT LCD colour screen with 600x1024px resolution that provide three calling methods: by entering the apartment number, searching in the contact list, or buttons.
- Modular graphic interface that allows to modify the main screen shortcuts.
- Inductive loop antenna for the heard impairment people.
- Presence sensor and ambient light sensor.
- Acoustic confirmation tones when display is pressed.
- RFID proximity reader for up to 2000 cards. 13,56 MHz cards are accepted.
- RJ-45 connector for programming.

Dimensions: 155(W) x 317(H) x 50(D)mm.

More information

- Wiegand26 connector for the video intercom and IP-Opener access control systems integration.
- CCTV input for an analogic camera.
- Possibility of displaying the door panel images in its own screen and customize the welcome screen image.
- Basic programming via the menu in the screen and advanced settings through the web client.
- Remote programming through the "Sixty5 cloud" website.
- Anti-sabotage alarm tamper.
- 12 Vcc input for local power.
- 2 relay contacts and 2 exit push button inputs.
- Requires a CE-6502 SE embedding box.

Accessories

- MAC-6502 adapter frame
- S7165 SE surface box with integrated rain shield
- 13.56MHz NFC/US proximity card
- UC-6502 CABLE TUNNELS SET
- CE-6502 SE embedding box for Sixty 5 door panels
- S7865 SE rain shield
- 13.56MHz TAGNFC/US proximity keyfob

Visit in the website: <https://www.golmar.es/products/6507-g2-plus>

Visit in the website: <https://www.golmar.es/products/6507-g2-plus>