

Bullet IP camera CIP-24B5MA2 PoE video analytics, 5Mpx



Reference: CIP-24B5MA2
Product code: 31691064
EAN code: 8429898022741



Main characteristics

- 1/2.8" progressive CMOS sensor
- H.265 / H.264 compression
- Proprietary protocol / Onvif 2.6
- 2.8 to 12mm autofocus motorized lense
- 109° to 32° horizontal angle of view
- Advanced video analytics (perimeter, cross line, pedestrian and face detection)
- Infrared illumination with 40m range
- IP66 protection rating
- Micro SD card slot
- Audio, reset, alarm and video output terminals
- Power-Out function
- Compatible with C-BASE01, C-BASE02 and C-BASE05
- Dimensions: 84(Ø) x 242(D) mm

More information

Visit in the website: <https://golmar.es/products/cip-24b5ma2>

Golmar Sistemas de Comunicación S.A.

Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • Fax: +34 934 742 404 • golmar@golmar.es • www.golmar.es

Specifications	
Type	Bullet
Technology	IP
Image sensor	1/2,7" progressive CMOS
Images by sec. (FPS)	30
Colour	White
Mounting	Wall
Lense	Motorized
Focal length	2.8-12mm
Zoom (x)	4
Max. Aperture ratio	1,8 - 3,3
Horizontal field of view (°)	107 - 34
Vertical field of view (°)	55 - 19
Minimum illumination (lux)	Color 0.01lux @ F1.2(AGC ON) ; B/N 0 lux @ IR ON
Night vision mode	Day/Night
IR distance max. (m)	45
WDR	Yes
Additional functions	AWB,BLC,AES,3D-DNR
Bitrate	256Kbps ~ 8Mbps
Main Stream (FPS)	30fps @ 5MP (2592x1944)
Sub Stream (FPS)	30 fps @ 720P (1280x720), VGA(640x480)
Video compression	H.264,H.265
Video Analysis	LCD,PID,PD,VD,FD,SOD,CC,CD,QD,HM
Internal storage	Yes (max 256Gb)
Network interface	RJ45
I / O alarms	1/1
I / O audio	1/1
Built-in microphone	No
Built-in speaker	No
Integrated WiFi	No
Remote Access / App	Web,App GolmarView,VMS Pro
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Compatibility	C-BASE01, C-BASE-02 and C-BASE05
Degree of protection (IP)	IP67
Material	Aluminium
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-35
Relative humidity work (max.)	95
Input voltage (V)	12Vcc,PoE
Included power supply	No
Rest consumption (W)	3
Max. consumption (W)	9
Dimensions - High (mm)	84
Dimensions - Width (mm)	87
Dimensions - Deep (mm)	242
Weight (gr.)	811
Certifications	CE,RoHS

Accessories

- C-BASE01 high junction box for camera
- C-BASE05 junction box for bullet
- SW-104 4-port PoE Switch
- C-BASE02 high junction box for camera
- AUDIO-BOX microphone and loudspeaker for CCTV applications

Visit in the website: <https://golmar.es/products/cip-24b5ma2>