

Dome IP camera CIP-24D5MA D/N 2.8-12mm motorized VA 5MPX



Reference: CIP-24D5MA
Product code: 31691030
EAN code: 8429898018539



Main characteristics

- Dome with video analysis and motorized lense 5Mpx
- 1/2.8" Progressive CMOS Sensor
- 2.8-12mm motorized autofocus optics
- Field of view 109° - 32°
- Compression H.265 / H.264
- Owner protocol / Onvif 2.6
- Advanced video analysis (perimeter, crossing line, stationary object, pedestrian detection, face detection, counter)
- 40 leds (SMD) / 40m
- Degree of protection IP66
- With audio terminal, reset, alarm, video output
- Dimensions 135 (Ø) x 120(P)mm
- Power supply 12Vcc / PoE

More information

Visit in the website: <https://golmar.es/products/cip-24d5ma>

Golmar Sistemas de Comunicación S.A.

Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • Fax: +34 934 742 404 • golmar@golmar.es • www.golmar.es

Dome IP camera CIP-24D5MA D/N 2.8-12mm motorized VA 5MPX



Specifications	
Type	Dome
Technology	IP
Image sensor	1/2,7" progressive CMOS
Images by sec. (FPS)	30
Colour	White
Mounting	Ceiling
Lense	Motorized
Focal length	2.8-12mm
Zoom (x)	4
Max. Aperture ratio	1,8 - 3,3
Horizontal field of view (°)	107 - 34
Vertical field of view (°)	55 - 19
Night vision mode	Day/Night
IR distance max. (m)	45
WDR	Yes
Additional functions	AWB,BLC,AES,3D-DNR
Bitrate	256Kbps ~ 8Mbps
Main Stream (FPS)	30fps @ 5MPx (2592x1944)
Sub Stream (FPS)	30fps @ 720Px (1280x720)
Video compression	H.264,H.265
Video Analysis	LCD,PID,PD,VD,FD,SOD,CC,CD,QD,HM
Internal storage	Yes (max 256Gb)
Network interface	RJ45
I / O alarms	1/1
I / O audio	1/1
Built-in microphone	No
Built-in speaker	No
Integrated WiFi	No
Remote Access / App	Web,App GolmarView,VMS Pro
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS
Compatibility	C-BASE02 and C-BASE04
Degree of protection (IP)	IP67
Material	Aluminium
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-35
Relative humidity work (max.)	95%
Input voltage (V)	12Vcc,PoE
Included power supply	No
Rest consumption (W)	3
Max. consumption (W)	9
Dimensions - High (mm)	127
Dimensions - Diameter (mm)	135
Weight (gr.)	846
Certifications	CE,RoHS

Accessories

- Wall mount bracket SP-24P for dome
- C-BASE04 high junction box for camera
- SW-104 4-port PoE Switch
- C-BASE02 high junction box for camera
- AUDIO-BOX microphone and loudspeaker for CCTV applications

Visit in the website: <https://golmar.es/products/cip-24d5ma>